

UNITED STATES UTILITY PATENT APPLICATION

FOR

**METHOD TO MAP AN INVENTORY MANAGEMENT SYSTEM TO A
CONFIGURATION MANAGEMENT SYSTEM**

Inventors:

Anna M. Zara

Sharad Singhal

Prepared by:


STATTLER, JOHANSEN & ADELI LLP
P.O. BOX 51860
PALO ALTO, CALIFORNIA 94303-0728
FAX: (650) 934-0475

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Express Mail Label No.: EL552915422US

Date of Deposit: May 10, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.


Shannon Lester

TITLE OF THE INVENTION

**METHOD TO MAP AN INVENTORY MANAGEMENT SYSTEM TO A
CONFIGURATION MANAGEMENT SYSTEM**

5

INVENTORS

Anna M. Zara, Sharad Singhal

1. Field of the Invention

The invention relates generally to processes for configuring and installing products in a data center or warehouse environment.

10

2. Background

15

20

Companies and other large entities increasingly rely on distributed computing where many user terminals connect to one or more servers that are centrally located. These locations called “data centers” may be facilities owned by the company or may be supplied by a third-party. These data centers house not only computers, but may also have persistent connections to the Internet and thus, conveniently house networking equipment such as switches and routers. Web servers and other servers that need to be network accessible are often housed in data centers. Where a third-party owns the data center, the entity in question rents a “cage” or enclosure that has racks upon which assembled/standalone units, such as computers and routers, can be installed. The entity may also simply lease the units that are rack-mountable from the third-party. In any case, the data center is usually divided into a number of predefined areas, including a shipping/docking area, assembly area, and area where enclosures and their constituent racks are kept.

25

Typically, the business process of installing and configuring new computer or networking systems involves a series of independent stages. First, based on determined requirements, components of the systems are ordered through a vendor or supplier. Once the components for these systems are received, inventory logs the “asset” tag for the component which identifies it for future reconciliation/audits. While the order for the components themselves may identify a number of attributes that each component should

have (i.e. amount of memory, number of ports, model number etc.), the inventory systems often do not, and may only be concerned with the fact that the item was in fact received, and what the serial number or other distinguishing identifier is. Conventional asset records track accounting information such as depreciation, but not other attribute
5 information.

Once a component or set of components is received it is installed in the data center. Installation and assembly of components that make up a deployable “asset” is not typically performed by those employed in the receiving/warehousing department or by those who track inventory. After the component is physically assembled or installed, it
10 will need to attain a “soft” configuration. The soft configuration includes attributes such as the IP (Internet Protocol) address, operating environment and so on. This soft configuration information frequently depends upon the attributes of the component. For instance, when installing software applications on a computing system asset (“compute node”), the operating system image to be deployed may depend on the size of the disk in
15 the asset. Similarly, the MAC (Media Access Control) address of the network interface card may be needed to give the asset a correct IP address. The current environment relies on highly skilled employees for all aspects of component assembly and configuration. Because such skilled workers are in short supply, the assembly and configuration of new components in a data center can take weeks.

20 The management system is the vehicle and charge of the administrative or Information Technology (IT) departments within a large entity such as a corporation. The management system must identify, once products are received, what they consist of, and how to configure or install them. This information must be either discovered by the management system or re-entered into the management system by the skilled workers
25 who configure and install the component. As is often the case, the skilled assembler must take the received components and inspect/test them to find out its attributes and configuration because the original order data and the received physical component cannot be easily correlated.

There is thus needed a more efficient configuration process that requires less use
30 of skilled workers and increases the reliability of the configuration job and time-to-deployment of components.

5 template.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a flowchart of the primary methodology in mapping an inventory management system to a configuration management system according to one or more embodiments of the invention.

5 **Figure 2** is a flowchart illustrating new unit discovery according to one or more embodiments of the invention.

Figure 3 is a flowchart illustrating associating of a node's configuration with the management system according to one or more embodiments of the invention.

10 **Figure 4** is a diagram illustrating the interaction of the systems involved in implementing the various embodiments of the invention.

Figure 5 is a diagram of a compute node which can be configured and managed in accordance with the various embodiments of the invention.

Figure 6 is a diagram of a computer implementation of one or more embodiments of the invention.

15

DETAILED DESCRIPTION

Referring to the figures, exemplary embodiments of the invention will now be described. The exemplary embodiments are provided to illustrate aspects of the invention and should not be construed as limiting the scope of the invention. The exemplary
5 embodiments are primarily described with reference to block diagrams or flowcharts. As to the flowcharts, each block within the flowcharts represents both a method step and an apparatus element for performing the method step. Depending upon the implementation, the corresponding apparatus element may be configured in hardware, software, firmware or combinations thereof.

10 The invention primarily consists of utilizing a management system to control the configuration and installation of software on a compute node. The management system maintains a database of asset records, and for each node, when the node is first requested or ordered, it creates an asset record and asset ID unique to that asset. The asset record is associated with the node based upon a certain parameter such the MAC address of the
15 node's NIC. Once a node is deployed it sends out a network request. Based on this request, the management system proceeds with a new unit discovery process. The management system then finds a configuration template suitable for the node. Finally, using the configuration template, software is automatically installed on the node.

20 **Figure 1** is a flowchart of the primary methodology in mapping an inventory management system to a configuration management system according to one or more embodiments of the invention. First, the inventory or ordering system will build a request for units to be deployed in a rack (block 110). For instance, if it were determined that a computer system needs to be deployed in a given rack, a request for that system is built. This type of request typically accompanies an order to a vendor for the components of the
25 unit. However, the unit can also be built based on components already in inventory. Thus, according to block 120, there is check as to whether the units (and their components) are in inventory. If the units are not in inventory, the management system must wait until the units are in inventory and ready for deployment (block 130). Once the units are in inventory, they are installed in the racks and powered-on (block 140).

At this point, the node has been bolted into a rack, has been plugged to power and networking and has been powered on. By using network messaging (described in detail with respect to **Figure 2**), the new unit will undergo a discovery process (block 150). In the new unit discovery, the unit will broadcast a message on the network requesting the management system to provide it with configuration data. The management system uses the information provided by the unit to find a configuration template for the discovered unit (block 160). The configuration templates are a series of configuration parameters and instructions that are stored/created for different classes or types of units. Depending upon the type, model or class of the unit, the management system or other specialized system (e.g., see software configuration system, described below) will find an appropriate configuration template (block 160).

Once a configuration template is found, the management system or other specialized system (e.g., see software configuration system, described below) will install software on the unit based on the parameters given by the template (block 170).

Alternatively, the management system may provide the unit with instructions on how to install this software. This automatic installation of software is made possible in a data center environment partially because the management system database contains information about the attributes (such as the MAC address of the network interface card (NIC) in the unit). Once the software is installed, the unit can signal to the management system that it is ready for use (block 180).

Figure 2 is a flowchart illustrating new unit discovery according to one or more embodiments of the invention. At this point the node has been bolted into a rack, an asset record (described in detail with respect to **Figure 3**) has been created, it has been plugged to power and networking and it has been powered on. The new unit discovery begins by checking if the node (unit as installed in the rack) requires soft configuration (block 210). An example of such a node is a “compute” node. A compute node is a unit that has large-scale data processing (computing) capability such as a personal computer system. Such nodes are often characteristic of servers and will often have one or more NICs (Network Interface Cards) which allow the node to communicate information on a network. The primary NIC will send out a network request (e.g. DHCP (Dynamic Host Control Protocol) request for an IP address) (block 220) which may also be accompanied by an

explicit request for configuration data. This signals the management infrastructure that a node is booting up and is ready to be configured.

The MAC (Media Access Control) address of the NIC is a device signature unique to the NIC. The MAC uniquely identifies the NIC to the management system. MAC addresses are assigned at the time of manufacture and are guaranteed to be globally unique. All network messages sent by the NIC contain its MAC address to allow other nodes to communicate back to it. When a primary NIC sends out a network request message, the management system will compare the MAC sent by the node with all the MACs that are known (block 230). The known MACs will be those of devices that are in inventory or have been received by the company and thus, are present in the management system database. If the MAC is not known, then one possible explanation is that an intruder has penetrated the network. Thus, in this case of an unknown MAC, the management system will begin intruder diagnostics (block 235). Each node with network access in a data center must connect to a known good switch, determining the switch of origin will allow the management infrastructure to determine the location of the intruder. All unknown MACs are assumed to be intruders until verification is complete and the management infrastructure is updated.

If the MAC is known, then using the MAC as a key (or indexing parameter) the asset ID of the node is found (block 240). The next test is to see whether the state information (associated by and stored along with the asset ID) for the node indicates that the node is in the initial state (block 250). The initial state is when the node is first installed in a rack. If it is not in the initial state, then a further check is performed to see whether the node's state information indicates that it is in a reinstall state (block 260). If the node is neither in reinstall nor initial states, then it indicates that the node is undergoing a reboot. In this case, the node is allowed to proceed with its normal boot process (block 270). If the node is either in reinstall state (checked at block 260) or in the initial state (checked at block 250), then software needs to be installed. When in a reinstall state, the node is configured in a like manner to the initial state with the exception that a node needs to be scrubbed (i.e. have its hard drive erased). Hence, to determine which software to install and the parameters thereof, the management system finds an appropriate configuration template for the discovered unit (block 280).

Figure 3 is a flowchart illustrating associating of a node's configuration with the management system according to one or more embodiments of the invention. First, the configuration template for a compute node (unit with computing capability) is defined (if it does not yet exist) or retrieved (if already present in the system) (block 310). This includes all optional (e.g. additional NICs, management cards) and configuration specifications (e.g. processor speed) for the node allowed by the manufacturer. Next, an asset record is created in the management system database with a specific and unique asset ID for the node (block 320). The asset record will track the configuration information (or pointers to the appropriate configuration template), soft configuration, state, asset ID, MAC and other pertinent information about the node. Each node has its own asset ID and asset record, which are all in one-to-one relationships with another. Once the asset record is created, all activities related to the node (which may or may not physically yet exist) can be tracked. After the asset record is created, the node is ordered or requested (block 330). As detailed information becomes available about the asset, it is entered in the asset record during each step of its purchase, assembly and installation. For example, the kind of processor in the asset or the amount of internal disk can be entered when the asset is ordered because that information is known when the purchase order is written. The ordering and receipt of the node can also be tracked within the created asset record. The management system can check to see if the node is received from the manufacturer after it has been ordered (block 340). If the node is not yet received, the management system must wait for receipt of the ordered node (block 350). If the node is received from the manufacturer (or vendor), then the assembly of the components into the requested node can be prepared for (for instance, if it has multiple components that need to be integrated together) (block 360). As part of this process, the bar-code information on the components is read and then the data therefrom is associated with the previously created asset record (block 370). Additionally, information about the MAC addresses of the NIC cards is recorded in the asset record. This allows the management system to find the soft configuration template associated with the node during the discovery process.

Next, the node is associated with the order's corresponding asset record (block 380). This allows the management system to associate other attributes of the node (e.g., processor type, amount of memory or internal disk) with the MAC address. The management system then waits for the node to be deployed in a rack on the data center floor (block 390). At this point the asset ID for the specific node has been associated with

all MACs that will be accessing the network from that node. The asset record contains the configuration information (or a pointer to the configuration template) so that the process of installing and configuring software on the newly deployed node can be automatically carried out by the management system (or other dedicated system such as a software configuration system, detailed below) when it requests configuration information over the network as it is powered up.

Figure 4 is a diagram illustrating the interaction of the systems involved in implementing the various embodiments of the invention. At the data center, an internal LAN (Local Area Network) Mechanism 430 is used for network communications. LAN mechanism 430 may consist of mechanisms such as Ethernet for carrying LAN information traffic and may include protocols for interaction between users of the LAN, such as TCP/IP or IPX. The LAN mechanism 430 ties together various servers, devices, nodes and rack locations of the data center. A new compute node 400 may be deployed within a given rack and may contain one or more NICs that allow it to communicate over LAN mechanism 430. A first primary NIC of new compute node 400 will connect the new compute node 400 to a primary switch 410 which may also be deployed in the same rack. The primary switch 410 is a part of the LAN mechanism 430 and connects the primary NIC to the LAN mechanism 430. The new compute node 400 may optionally have a secondary NIC which will connect it to a secondary switch 420. The secondary switch 420 may also connect the secondary NIC to the LAN mechanism 430. Alternately the secondary switch 420 may connect the secondary NIC to a different LAN mechanism or network.

LAN mechanism 430 allows other systems such a software configuration system 440 and a management system 450 to be connected to each other and to new compute node 400. The software configuration system 440 serves applications and performs installs of applications to nodes. The management system 450 has database server software, which manages asset records that can be stored in a datastore 460 (e.g., a database). During new unit discovery, the management system 450 responds to a network request from the new compute node 400, once deployed in its rack. The management system 450 then compares the MAC of the primary NIC of compute node 400 with a list of MACs for known devices which may be stored in datastore 460. If known, the management system 450 finds the appropriate asset ID (and, consequently,

asset record) associated with the node 400. It then sends a message to compute node 400 with pointers (contained in the asset record) to the correct software in the software configuration system 440. In one embodiment of the invention, the software configuration system may be a tftp (Trivial File Transfer Protocol) server. The compute node then requests the software configuration system for the software and loads it. Depending on the configuration, the node may also request other software from the software configuration system, or alternatively, the software configuration system may install other software on node 400.

The management system 450 is also responsible for tracking and maintaining state information regarding the new compute node 400. This state information can be stored in datastore 460 in an asset record corresponding to the new compute node 400. If the management system 450 determines, for instance, that the new compute node 400 is in an initial state, it will initiate software configuration system 440. The management system 450 will find a configuration template that corresponds to the asset class/type of the new compute node 400 which would be designated in its asset record. The configuration template that is found will then form the basis by which the software configuration system 440 decides how and what software will be installed onto new compute node 400. The software configuration system 440 then installs, automatically, the desired software onto the new compute node 400.

The management system 450 also initially creates the asset record at the time the new compute node 400 is requested or ordered, and maintains in that asset record any post-deployment information that would be desirable for further installation, monitoring or maintenance of the new compute node 400. The software configuration system 440 will contain installable versions of the software that is to be installed on nodes and application software that controls the installation process.

Figure 5 is a diagram of a compute node which can be configured and managed in accordance with the various embodiments of the invention. The compute node 500 has a number of components such as a CPU (Central Processing Unit) 510 and RAM (Random Access Memory) 520. The compute node 500 also has a bus 580 that allows these components and others to communicate with each other. For instance, compute node 500 is shown having two NICs, a primary NIC 540 (so called because it is in the primary slot)

and a secondary NIC 550. Each of these NICs are connected to other components within the node and to a LAN (Local Area Network) 590. LAN 590 is shown merely as an example of the possible networks that the NICs may connect to. Each of NICs 540 and 550 may instead connect to separate networks. For instance, the primary NIC 540 may be
5 connected to LAN 590 while the secondary NIC 550 is connected to a WAN (Wide Area Network) such as the Internet. Bus 580 also connects other peripheral components such as a disk 530, which is non-volatile storage mechanism such as a hard drive.

In accordance with the invention, the compute node 500 may be assembled of the components—such as CPU 510, RAM 520, disk 530, primary NIC 540 and secondary
10 NIC 550. Prior to assembly, the bar-code information for these components may be scanned and used to create asset record. When finally deployed, the compute node 500 will send a network request message through either NIC 540 or NIC 550. The management system will located the correct soft configuration information for the node using the MAC address of the NIC that sent the request. Next, the management system
15 and software configuration system will install applications onto disk 530 of node 500 through one or both of the two NICs 540 and/or 550. If the MAC address of the NIC is not known to the management system, the management system may flag the request as a possible intrusion, and start appropriate security measures. Once these applications, such as operating system software, are configured on the node 500, it is then completely
20 deployed as an operational part of its rack and of the data center in which its rack is housed. The CPU 510, RAM 520 and/or disk 530 may be of such a type, speed and capacity that would warrant installing only certain software or only certain optimized or un-optimized versions of the same software. The management system would be able to determine such parameters of the install based upon the asset information about the node
25 500 that is contained in its asset record.

When the compute node 500 boots, the components attached to the internal bus 580 become active in a specific order. Ordinarily, the primary NIC 540 being in the primary slot becomes active and can communicate with the LAN 590 before the compute node 500 is fully booted. This allows for the primary NIC 540 to act as a gateway for a
30 new soft configuration for the node 500 to be done (soft configuration includes network identity, operating system, applications, etc.).

Figure 6 is a diagram of a computer implementation of one or more embodiments of the invention. Illustrated is a computer system 607, which may be any general or special purpose computing or data processing machine such as a PC (personal computer), coupled to a network 600. One of ordinary skill in the art may program computer system 607 to act as a management system server and/or a software configuration system server. The management system server and software configuration system server, are, in accordance with some embodiments of the invention, two separate and independently operating systems. However, it will be readily apparent that the functionality of both the management system and the software configuration system can be integrated onto as services of a single physical computer system such as system 607. According to one or more embodiments of the invention, the system 607 or systems similar to it, would be programmed to perform the following functions when implementing a management server:

- Building an asset record for an ordered/requested node;
- Receiving a network request from a deployed node;
- Comparing the MAC associated with received network requests with known MACs;
- Interacting, managing and maintaining a database of asset records;
- Determining, maintaining and updating state information regarding nodes; and
- Finding a software configuration template that corresponds to a node needing software installation.

According to one or more embodiments of the invention, the system 607 or systems similar to it, would be programmed to perform the following functions when implemented as a software configuration system server:

- Reading parameters contained in a software configuration template;
- Installing software applications on nodes needing such installation;

- Reinitializing non-volatile storage mechanisms in nodes already having installed software but desiring a re-install;
- Configuring said software applications during and after installation; and
- Upgrading or reconfiguring installed software applications on nodes when so desired.

In either role, system 607 has a processor 612 and a memory 611, such as RAM, which is used to store/load instructions, addresses and result data as desired. The implementation of the above functionality in software may derive from an executable or set of executables compiled from source code written in a language such as C++. The instructions of those executable(s), may be stored to a disk 618, such as a hard drive, or memory 611. After accessing them from storage, the software executables may then be loaded into memory 611 and its instructions executed by processor 612. The result of such methods may include calls and directives in the case that the asset records (and related information such as software configuration templates) are stored on disk 618, or a simple transfer of native instructions to the asset records database via network 600 if it is stored remotely. The asset records base may be stored on disk 618, as mentioned, or stored remotely and accessed over network 600 by system 607. Also, installable versions of software applications that are to be installed on deployed nodes may be stored on disk 618, as mentioned, or stored remotely and accessed over network 600 by system 607.

Computer system 607 has a system bus 613 which facilitates information transfer to/from the processor 612 and memory 611 and a bridge 614 which couples to an I/O bus 615. I/O bus 615 connects various I/O devices such as a network interface card (NIC) 616, disk 618 and to the system memory 611 and processor 612. The NIC 616 allows software, such as server software, executing within computer system 607 to transact data, such as requests for network addressing or software installation, to nodes or other servers connected to network 600. Network 600 is also connected to the data center or passes through the data center, so that sections thereof, such as deployed nodes placed in racks and management and software configuration systems, can communicate with system 607.

The exemplary embodiments described herein are provided merely to illustrate the principles of the invention and should not be construed as limiting the scope of the

invention. Rather, the principles of the invention may be applied to a wide range of systems to achieve the advantages described herein and to achieve other advantages or to satisfy other objectives as well.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238